

SALIENT FEATURES :

- INCREASES PRODUCTIVITY
- SORTS OUT WASTAGES & FINES
- INCREASES EFFICIENCY OF MACHINE AT PRIMARY OR SECONDARY STAGE CRUSHERS
- CONTINUOUS FEEDING OF MATERIAL

MOST VERSATILE AND RELIABLE



MOD.

VIBRATING & RECIPROCATING FEEDERS

VIBRATING & RECIPROCATING FEEDERS (EFD & RFD)



An ISO 9001 Company

TECHNICAL SPECIFICATIONS

VIBRATING FEEDER

The vibrating action of the feeder conveys material while separating loose fines. This provides smooth, controlled feed rates to maximize capacity of the plant. The fines drop to the bottom of the feed material and are passed through the grizzly section. Grizzly bars are tapered to improve scalping action. Bar spacing is adjusted for controlled fines removal. Heavy duty spring suspension provides protection and cushioning against impact and vibration.

VIBRATORY MOTOR FEEDER SPECIFICATIONS

MODEL NO.	SIZES	CAPACITY TONS / HOUR	MOTOR HP
EFD 752	0.75 MTR X 2 MTR	40 - 80	0.57 KW (2 nos.)
EFD 103	1 MTR X 3 MTR	80 - 125	1 KW (2 nos.)
EFD 124	1.2 MTR X 4 MTR	125 - 200	3.3 KW (2 nos.)
EFD 144	1.4 MTR X 4 MTR	200 - 350	3.3 KW (2 nos.)

RECIPROCATING FEEDER SPECIFICATIONS

MODEL NO.	SIZES	CAPACITY TONS / HOUR	MOTOR HP
RFD 2060	20" X 60"	10 - 25	3
RFD 3072	30" X 72"	25 - 60	5



Reciprocating Feeder (RFD)



Grizzly Feeder (EFD)



MANUFACTURED BY:



Head Office :

N-16, M.I.D.C. Indl. Area, Ambad, Nashik - 422 010. (M.S.) INDIA

Tel. : +91-253-2382940. Fax : +91-253-2380272.

E-Mail : sales@marsmanltd.net, info@marsmanltd.net

Website : www.marsmanltd.net

Works:

Unit I : Gat. No. 581/582, At Post Janori, 10th Mile, Ozar, Mumbai-Agra Road, Nashik - 422 206. (M.S.) INDIA.

Tel.: +91-2557-275210.

Unit II : Plot No. 712, G.I.D.C., Savli, Manjusr, Dist. Baroda-319 775. (Gujrat) INDIA.

Tel. : +91-2667-292123. E-mail : baroda@marsmanltd.net